

Submersible Capacitive Transmitters

For water level measurements

Series 46X

Series 46X-Ei

The Series 46X combines the ceramic measuring cell for low pressure ranges with the μ P-electronics of the digital Series 30 pressure transmitters. The signal values of the pressure- and temperature sensors are determined by a polynomial compensation¹⁾. The values can be shown and stored on a PC and can be reprogrammed. A reference tube integrated in the cable connects the referential chamber of the sensor with the ambient pressure.

Specifications

Pressure Ranges (FS)*	30	100	300	mbar
Overpressure	300	1000	1500	mbar

* Intermediate ranges for the analog output are realizable with no surcharge by spreading the standard ranges (note that the error band will then increase proportionally)

Type	2-Wire	3-Wire
Supply (U_B) 46X	8...28 VDC	13...28 VDC
Supply (U_B) 46X-Ei	10...30 VDC	15...30 VDC
Signal Output (scaleable)	4...20 mA	0...10 V
Load Resistance	$<(U_B - U_{Bmin}) / 20 \text{ mA}$	$\geq 100 \text{ k}\Omega$
Error Band max. **	$\pm 0,2 \text{ \%FS}$	$\pm 0,2 \text{ \%FS}^{***}$

** Within the compensated temperature range

*** 46X-Ei: Without load on the voltage output ($R_i = 100 \Omega$)

Stability	FS $\geq 100 \text{ mbar}$: $\pm 0,1 \text{ \%FS}$	FS $\leq 100 \text{ mbar}$: $\pm 0,1 \text{ mbar}$
-----------	---	---

Operating Temperature	0...80 °C (icing not permitted)
Compensated Range	10...50 °C


Electrical Connection	- Reference cable PE sheath $\varnothing 5,8$ - Cable length: Standard 5 m
Materials Contact with Media	- Housing: Stainless steel (type AISI 316L) - Diaphragm: Ceramic, gold plated - Nitrile O-ring
Protection	IP68
Weight	$\approx 400 \text{ g}$ with 5 m cable
Options	Programmable, other versions

This pressure transmitter is also available as an intrinsically safe version (Series 41X-Ei) and can be used as a partition wall device at the border of Zone 0 and Zone 1. Pressure transmitters in the 41X-Ei series may only be used in conjunction with proven intrinsically safe equipment. Observe the operating instructions.

¹⁾ More information about the polynomial compensation and associated software you will find in the Series 41X datasheet.



II 1/2 G
 Ex ia IIC T4 Ga/Gb
 PTB 06 ATEX 2011 X
 IECEx PTB 21.0018 X
 EPS 23 UKEX 1 183 X



Electrical Connections

	2-Wire	3-Wire
Black	+VCC	+VCC
White	OUT/GND	GND
Red		+OUT
Blue	RS 485 A	
Yellow	RS 485 B	